

CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL
FIRE ENGINEERING - BUILDING MATERIALS LISTING PROGRAM

LISTING SERVICE

LISTING No. 3230-0273:110 Page 1 of 1

CATEGORY: Leakage Dampers

LISTEE: United Air, PO Box 40913, Nashville TN 37204
Contact: *Jon Newnam (615) 256-3500 Fax (615) 242-3806

DESIGN: Models D-501, D-502, D-503, 501, 502 and 503 leakage rated dampers. Refer to listee's data sheet for detailed product description and operational considerations.

<i>Model</i>	<i>Single Section Width</i>				<i>Multiple Section Height</i>			
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
501	8"	36"	8"	48"	36"	72"	8"	48"
502	6"	36"	8"	48"	36"	72"	8"	48"
503	6"	44"	6"	53"	12"	72"	6"	53"
D501	8"	36"	8"	48"	36"	72"	8"	48"
D502	6"	36"	8"	48"	12"	72"	8"	48"
D503	6"	44"	6"	48"	12"	72"	6"	48"

RATING: 501: Class I-250, I-350
502: Class II-250, II-350
503: Class III-250, III-350
D501: Class I-250
D502: Class II-250
D503: Class III-250

INSTALLATION: In accordance with listee's printed installation instructions, applicable codes and ordinances and in a manner acceptable to the authority having jurisdiction.

MARKING: Listee's name, model number, classification rating and UL label.

APPROVAL: Listed as leakage-rated dampers for use in air conditioning and ventilating ducts to protect openings in fire resistive walls, partitions or floors. Suitable for vertical and horizontal installation.

*Rev. 06-08-2002



This listing is based upon technical data submitted by the applicant. CSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

Date Issued: **JUNE 13, 2003**

Listing Expires **June 30, 2004**

Authorized By: **DIANE K. AREND, Senior Deputy
Program Manager**